

## → Columbia Aqua Dispenser

# **FC 825 UV UF**

## (Ref. 796839)







#### **DESCRIPTION**

Cold, hot and ambient water dispenser.
Equipped with reverse osmosis system and booster pump.
Tactile selection buttons. Energy saving system.
Wide space fot bottles and energy saving.

#### **CHARACTERISTICS**

TEMPERATURE	Cold - Hot - Ambient
OPERATING SYSTEMS	Ultrafiltration
ELECTRICAL POWER SUPPLY	220-240 VAC / 50 Hz
COLD WATER TEMPERATURE	4 - 13°C
COOLING CAPACITY	10 L/H
HEATING CAPACITY	7 L/H
TEMPERATURE CONTROL	Temperature sensor
COLD WATER TANK	11 Liters
HOT WATER TANK	3 Liters
INLET/DRAIN CONNECTION	1/4"
COLD WATER TANK MATERIAL	AISI 304 stainless steel
COMPRESSOR POWER	150W
HEATING POWER	800W
REFRIGERANT COMPRESSOR	R - 600a (37 gr.)
HOT WATER TEMPERATURE	80 - 85°C
REFRIGERATION SYSTEM	Heat pump
HEATING SYSTEM	Electrical resistance in tank
WEIGHT	30 Kg
PRESENTATION	Floor Standing
WATER TREATMENT SYSTEM	1 filter 5 micron – 796330 1 block carbon filter – 796331 1 UF Filter – 796332
GERMICIDAL SYSTEM	2 UV LED Inside cold water tank 1 UV LED at the outlet



**ENERGY SAVING** 



ULTRAFILTRATION



TRIPLE UV LED MAXIMUM PROTECTION




HOT WATER SAFETY SYSTEM



ANTI-FLOOD SENSOR



TACTILE BUTTON





INLET WATER PRESSURE (max-min)	6 ~ 1 BAR
INLET WATER TEMP. (max-min)	38°C ~ 4°C
AMBIENT TEMP. (max)	43°C





WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).