



→ Direct Flow Reverse Osmosis.

COMMERCIAL 1000 GPD

(Ref.910696)

DESCRIPTION

Reverse osmosis system.
Direct flow.
Low cost maintenance.
Long-lasting filters and membranes.
Great design and versatility.

SPECIFICATIONS

| WEIGHT | 10.7 kg |
|-----------------------------|------------------------------------|
| RO WATER PRODUCTION | 2,4 lpm |
| REJECT | 1 lpm |
| INLET TEMPERATURE (maxmin.) | 38 °C - 5 °C |
| INLET TDS (max.) | 1500 ppm |
| INLET PRESSURE | 4 bar - 1 bar (400kPa - 100kPa) |
| MEMBRANE | 1000 GPD |
| POWER SUPPLY | 36 Vdc |
| EXTERNAL ADAPTER | 230 Vac 50 / 60 hz / 36 Vdc |
| EXTERNAL PROGRAMMER | Smart DOT. Notices and adjustments |

ORIGINAL CONSUMABLES

Combi sediments + carbon block (cód. 910465)

Membrane RO 1000GPD (Ref.910706)



FILTERED WATER



RO WATER



FILTER CONTROL



QUALITY CONTROL



SOUND WARNINGS



LED STATUS



HIGH EFFICIENCY RECOVERY




AQUASTOP



ELECTRONIC ADAPTER





EXTERNAL TOUCH INTELLIGENT





WLG (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations). WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.