

→ Direct Flow Reverse Osmosis

## **RO KUBE BLACK**

(Ref.911230)

## **SPECIFICATIONS**

PRODUCTION	2 lpm
WEIGHT	12 kg
INLET TEMPERATURE (máxmín.)	38°C / 5°C
INLET TDS	1500 ppm
INLET PRESSURE	4 bar - 1 bar (400kPA-100kPa)
FAUCET	1 way Electronic Faucet
PUMP	High performance Diaphragm Booster Pump
POWER SUPPLY	24 Vdc
EXTERNAL ADAPTER	100-240V. 50/60Hz: 24Vdc
MEMBRANE	800 GPD
PREFILTER	Mixed pp 10 microns+high quality carbon fiber
POSTFILTER	High quality carbon block



4 Stage cartridge RO KUBE DIRECT FLOW combi CFRO (Ref. 910745)





Filter life

pre-warning

Normal

operation





WLG (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC Certif. no 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).

End of filter life