

43 OLI I 1000 evo







PRODUCTION



HEALTHY

WATER







SIZE COMPACT

E ACT MAXIMUM SAVINGS

Weight:
Inlet temperature:
Inlet TDS:
Inlet pressure:

Membrane:

Flow rate:

Membrane:
Power supply:

External power adapter:

Pump

Pre-filter + Post-filter:

2.4 LPM.

11 kg.

Min: 5 °C / Max: 38 °C.

1500 ppm. 4 - 1 BAR.

1000 GPD.

24 Vdc 7A 168W.

200-240V. 50/60Hz.

High-performance diaphragm booster pump. Filter composed of 5-micron pre-filtration, activated

carbon block, and anti-scaling beads + activated carbon

post-filter.

BOLT 1000 evo

FILTER CONTROL

QUALITY CONTROL

AUDIBLE ALERTS

SMART TAP

LED STATUS

SAFETY LOCK

ANTI-SCALE BEADS

YOUR WATER UNDER CONTROL, IN AN INTELLIGENT WAY

Information display: shows the status of the filters and water quality in real time.

Efficient control: optimizes water use

and protects your installation.

Integrated alarm system.

Practical design: modern, durable, and

easy to install.

GENERAL

SCREEN

INFORMATION



FILTER STATUS

TDS mg/L

000



MEMBRANE STATUS

Drocesses

1 - COMBINED FILTER

PP + CARBON + ANTI-SCALE + POST-CARBON

This filtration system removes sediment, corrosion, chlorine, and solid particles from the water, ensuring a cleaner and safer supply. It also reduces unwanted odors and tastes, significantly improving water quality.

In addition, it protects equipment components, helping to prevent damage and extending their useful life.

2 IN 1

2 - MULTIFUNCTION MEMBRANE HIGH EFFICIENCY

Removes organic compounds and microorganisms present in the water, ensuring a cleaner, safer, and higher quality supply.

WATER QUALITY INDICATOR

ADVANCED FILTRATION, **GUARANTEED RELIABILITY**



