

Mach 2100s


This commercial softener can be configured to either an Overdrive or Alternating set-up.

- High flow rate and easy to maintain.
- Twin-tank, non-electric water softener.



Specifications:

Dimensions		
System (w x d x h)	533 x 254 x 1524 mm	
Weight	79 - 159 kg	
Type	Standard	Overdrive
Performance		
Minimum Flow	1,1 l/min	1,1 l/min
Maximum Flow @ 1 Δ bar	45 l/min	79 l/min
Hardness as CaCO₃ (max)	1830 mg/l	975 mg/l
Regeneration		
Salt Used / Capacity	2,5 - 6,8/114 kg	2,5 - 6,8/114 kg
Time	90 minutes	90 minutes
Volume	386 litres	386 litres
System		
Media Volume	2 x 42 litres	2 x 42 litres
Inlet/Outlet Connections	Custom	Custom
Maximum Temperature	50°C	50°C
Inlet Pressure (Min/Max)	1,0 / 8,6 bar	1,0 / 8,6 bar



2

901608

Mach 2175s


The Mach 2175s has been designed with an extra large salt capacity to cope with extreme levels of hardness.

- Extra large capacity tanks for salt storage.
- Twin-tank, non-electric system with large salt storage.



Specifications:

Dimensions		
System (w x d x h)	686 x 330 x 1524 mm	
Weight	136 - 204 kg	
Performance		
Minimum Flow	1,1 l/min	
Maximum Flow @ 1 Δ bar	61 l/min	
Hardness as CaCO₃ (max)	2993 mg/l	
Regeneration		
Salt Used / Capacity	6,8 - 13,6 / 227 kg	
Time	90 minutes	
Volume	538 litres	
System		
Media Volume	2 x 64 litres	
Inlet/Outlet Connections	Custom	
Maximum Temperature	50°C	
Inlet Pressure (Min/Max)	2,0 / 8,6 bar	



1

901609