

Mach 2030s


An advanced commercial water softener, the Mach 2030s is flexible in both set up and operation.

- Small but powerful water treatment unit.
- Twin-tank, non-electric water softener.



Specifications:

Dimensions	
System	381 x 178 x 1041 mm
Weight	47,6 - 64 kg
Performance	
Minimum Flow	1,1 l/min
Maximum Flow @ 1 Δ bar	34 l/min
Hardness as CaCO₃ (max)	770 mg/l
Regeneration	
Salt Used / Capacity	0,82 - 1,4 / 114 kg
Time	40 minutes
Volume	110 litres
System	
Media Volume	2 x 13,3 litres
Inlet/Outlet Connections	Custom
Maximum Temperature	50°C
Inlet Pressure (Min/Max)	1,0 / 8,6 bar



3

901606

901613

Mach 2060s


The Mach 2060s can operate in either a maximum flow or maximum efficiency configuration.

- Twin-tank, non-electric water softener.
- Large capacity tanks for salt storage.



Specifications:

Dimensions		
System (w x d x h)	432 x 203 x 1168 mm	
Weight	64 - 91 kg	
Type	Standard	Overdrive
Performance		
Minimum Flow	1,1 l/min	2,8 l/min
Maximum Flow @ 1 Δ bar	44 l/min	78 l/min
Hardness as CaCO₃ (max)	1129 mg/l	515,52 mg/l
Regeneration		
Salt Used / Capacity	1,2 - 2,0/114 kg	1,2 - 2,0/114 kg
Time	45 minutes	45 minutes
Volume	132 litres	132 litres
System		
Media Volume	2 x 19,8 litres	2 x 19,8 litres
Inlet/Outlet Connections	Custom	Custom
Maximum Temperature	50°C	50°C
Inlet Pressure (Min/Max)	1,0 / 8,6 bar	1,0 / 8,6 bar



3

901607

901614