

→ Columbia Aqua

FC 750F - FC 750 ROP


Filtration - Ultrafiltration - Reverse Osmosis (Ref.754332 - 754333 - 754329)

FEATURES

FC 750 F - FC 750 UFC 750 ROP

TEMPERATURE	Cold -Hot	Cold -Hot
WORKING SYSTEMS	Filtration - Ultrafiltration	Ósmosis inversa
COLD WATER TEMPERATURE	4 - 12°C	4 - 12°C
COOLING CAPACITY	5 L/H	5 L/H
TEMPERATURE CONTROL	Thermostat	Thermostat
COLD WATER TANK CAPACITY	3 Liters	3 Liters
COLD WATER TANK MATERIAL	AISI 304 stainless steel	AISI 304 stainless steel
COMPRESSOR	Sealed type. 100W	Sealed type. 100W
COMPRESSOR REFRIGERANT	R - 134a (34g)	R - 134a (34g)
HOT WATER TANK CAPACITY	1,8 Liters	1,8 Liters
HOT WATER TEMPERATURE	80 - 85°C	80 - 85°C
HEATING CAPACITY	7 L/H	7 L/H
TEMPERATURE CONTROL	Bimetal	Bimental
HEATER TYPE	Stainless steel band system AISI 304. 430W	Stainless steel band system AISI 304. 430W
BOOSTER PUMP	No	Yes
WEIGHT	22 Kg	22 Kg
PRESENTATION	Floor	Floor
WATER TREATMENT SYSTEM	5 micron 2'5 x 11'5 filter x 1 GAC 2'5 x 11'5 filter x 1 UF Membrane x 1 (only 754333)	5 micron 2'5 x 11'5 filter x 1 GAC 2'5 x 11'5 filter x 1 80 GPD membrane x 1 Alkalinizer 2'5 x 11'5 filter x 1









WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights Operator with number ESAEOF1800008U6 and 13/02/2018 as a date of entry of the authorization.