

→ Direct Flow Reverse Osmosis

## **RO BOLT 800 GPD**

(Ref. 910680)

## **SPECIFICATIONS**

RO WATER PRODUCTION	2,3 lpm
WEIGHT	7 kg
INLET TEMPERATURE (maxmíi.)	38°C / 5°C
INLET TDS (max.)	1500 ppm
INLET PRESSURE	4 bar - 1 bar (400kPA-100kPa)
MEMBRANE	800 GPD
FAUCET	Smart faucet + UV Led
PUMP	High performance Diaphragm Booster Pumo
POWER SUPPLY	24 Vdc
EXTERNAL ADAPTER	100-240V. 50/60Hz: 24Vdc
PREFILTER	Triple. 5 micron filtration, carbon activated block 10 microns and postfilter activated carbon block 10 microns

## **ORIGINAL CONSUMABLES**

PRICE (RATE A) Triple PP prefilter + carbon + postfilter (Ref. 910718) 33€ Membrane RO 800 GDP (Ref. 910719) 190€

## MAINTENANCE NOTICE SYSTEM

11 MONTHS - Maintenance light warning system 12 MONTHS - Acoustic maintenance warning system 15 MONTHS - Computer lock

Security lock for high consumption - The system gives you a warning when consuming 5000 liters to prevent chlorine from entering the membrane



**FILTER** CONTROL



QUALITY CONTROL



SOUND WARNINGS



SMART **FAUCET** 



LED STATUS




**SECURITY** LOCK



HIGH **EFFICIENCY** 



**AQUASTOP** SYSTEM



UV LED





WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).





