

## → Reverse Osmosis

## RO CELER (Ref. 910420)

**Direct Flow System** 

## **DESCRIPTION**

Advanced direct flow RO system
Unlimited instantly water
Without accumulation tank
Electronic faucet
Quality water and filter lifespan warnings

## **SPECIFICATIONS**

DIMENSIONS	385 mm x 160 mm x 465 mm
WEIGHT	16 kg
FLOW	1,65 LPM
INLET TEMPERATURE	38 ° C - 5 °C
INLET TDS	1500 ppm
INLET PRESSURE	1 / 4 bares 100 - 400 kPa
FILTER	PP+activated carbon
MEMBRANE	600 GPD
FAUCET	Smart faucet
PUMP	Booster
POWER SUPPLY	24 Vdc 95 W
ADAPTER	110 - 240V. 50/60Hz 24 W.



600 GPD Membrane (Ref. 910426)

Sediments + carbon filter (Ref. 910425)









AQUASTOP



DIRECT FLOW



STATUS



HIGH PERFORMANCE MOTOR




CAPSULATED MEMBRANE



SMART FAUCET



465mm







Water Quality Association.

WLG (B-60326279), is member of the



ACREDITED BY ENAC Certif, nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).