

## → Compact Hydraulic

## TOREN 11

(Ref.903076)

WATER SOFTENER

## **FEATURES**

| WEIGHT                  | 30 kg                       |
|-------------------------|-----------------------------|
| RESIN VOLUME (I.)       | 10,5 liters                 |
| PRESSURE (MAX-MIN)      | 1,7 - 8,6 bar               |
| WORK FLOW               | 2,1 m³/h                    |
| WORK MAXIMUM FLOW       | 2,3 m³/h                    |
| MAXIMUM HARDNESS        | 73°HF                       |
| INTERCHANGE CAPACITY    | 23,7°HFxm³                  |
| SALT / REGENERATION     | 0,36 kg salt                |
| WATER CONSUMPTION / REG | 25 liters                   |
| REGENERATION TIME       | 15 min                      |
| ROOM TEMPERATURE        | Protection against freezing |
| TEMPERATURE RANGE       | 2 - 40°C                    |

| 15°HF | 20°HF | 25°HF | 30°HF | 40°HF | 50°HF | 60°HF | 70°HF |
|-------|-------|-------|-------|-------|-------|-------|-------|
| 1250  | 938   | 750   | 625   | 469   | 375   | 313   | 268   |












HIGH SPEED Regeneration in 15 min.



LOW CONSUMPTION Low salt consumption



HIGH FLOW Ideal for your home







WLG (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC Certif. no 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).









WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF1800008U6 and 13/02/2018 as a date of entry of the authorization.